

# CD850 2.0

### DRIVER

#### **DESCRIPTION**

The CD850 2.0 is a high performance 3.0-inch diaphragm compression driver with a 2 inch exit throat featuring several state of the art technologies.

The diaphragm are precision formed from pure titanium. The suspension is based on a vented and damped design in order to provide low distorsion. Voice coil assembly is designed using high temperature kapton former.



#### **FEATURES**

- 3-inch Diaphragm, 2-inch Exit Throat / Pure Titanium Compression Driver
- 220W continuous program power handling
- Frequency range: 500Hz 20kHz
- 3-slot optimized geometry phase plug
- Ceramic Magnet Assembly
- Copper inductance ring for extended response
- Vented, damped, low distortion suspension system



#### **TECHNICAL SPECIFICATIONS**

General specifications	Exit Throat Diameter:	2.0 inch / 51 mm
	Related Impedance:	8 ohm
	Program Power (watt):	220 W
	Power handling capacity (watt):	110 W
	Sensitivity:	109 dB
	Frequency range:	500 - 20000 Hz
	Diaphragm Material:	Pure Titanium
	Suspension Material:	Polyester
	Suspension Design:	Flat
	Minimum Impedance (ohm):	8.50 ohm
	Voice Coil Diameter:	3.0 inch / 76 mm
	Voice Coil Material:	Edgewound Aluminium
	Voice Coil Former Design:	Straight - Kapton
	Number of layers:	1
	Kind of layers:	outside
	Flux Density:	1.9 T
	Phase Plug Design:	3 slot
	Phase Plug Material:	PP Composite
	Magnetics:	Ceramic
	Voice Coil Demodulation Ring	Copper
Thiele - small parameters	BI factor (BI) (T x m):	12.30 T x m
Mounting informations	Overall diameter:	180 mm / 7.09 inches
	Overall height:	88 mm / 3.46 inches
	Mounting:	4 x 6 mm threaded holes at 90°
Standard compliance	CE marking:	Yes
Size	Weight:	5.72 kg / 12.61 lbs
Shipping informations	Package Height:	119 mm / 4.69 inches
	Package Width:	214 mm / 8.43 inches
	Package Depth:	214 mm / 8.43 inches
	Package Weight:	5.97 kg / 13.16 lbs

## **PART NUMBER**

• 15129044

CD850 2.0 8ohm

